

CLOPAY COMMERCIAL – MODELS CERD10, CERD20 rolling steel series

The Clopay logo consists of a stylized 'C' icon followed by the word 'Clopay' in a bold, sans-serif font, all contained within a yellow rectangular box with a black border.

FIRE DOORS

- Manufactured to the stringent qualities of full-duty service doors, yet easily meet the most current fire protection standards.
- Operational choices include fail-safe motor-operated systems, hand crank (manual) and standard chain hoist operated systems.
- UL, FM and ULC labeled for fire protection up to four hours to meet today's fire protection demands.
- Clopay fire doors and shutters may be easily and repeatedly drop tested and reset from the floor with no tool or equipment requirements.
- The service durability, simplicity of ownership and proven fire protection with E-Z reset option [standard on doors larger than 9'x 9' (2.7 m x 2.7 m)] make Clopay fire doors a logical choice for informed design professionals.

clopaycommercial.com

Clopay fire doors feature UL and ULC labels for standard and oversized openings and may also be “S Labeled” for air and smoke infiltration. These fire protection systems are demonstrated and tested for full compliance with UL and NFPA-80 standards both in the plant and at testing facilities for reliable activation, drop speed, repeatability and endurance.

- Labeled fire protection for up to 4 hours
- Floor level drop test and reset
- Full-duty service engineering
- Weldable guides with upward expansion
- Guide service cutouts for ease and safety of service
- Structural steel construction
- Finish coated steel curtains and hoods
- Custom designed headplates designed for each door assembly; headplate designs for simplicity of operator installation
- Powder coated guides, bottom bars and headplates
- Formed metal hoods finished to match curtains
- Steel gauge per UL Listing for door size; available in 18, 20 and 22 gauge galvanized steel, or 20 gauge stainless steel #5 flat slat
- Model CERD20 (insulated door) contains 7/8" (22.2 mm) thick mineral wool insulation; available in 22 and 24 gauge exterior, 22 and 24 gauge interior skin

CHAIN HOIST MODEL

The bar has been raised for entry-level fire protection with the Model CERD10 or CERD20 (insulated) fire door. This rugged, gear reduced chain hoist system is designed for everyday use and features a truly remarkable governing system capable of handling fire door sizes to 256 square feet and beyond. As simple to install and own as a chain hoist driven service door, these fire door systems will meet your every expectation.



DISTRIBUTED BY:

MOTOR OPERATED MODELS

Using a planetary gear reduction system and a dependable, time-proven internal centrifugal braking governor, the CERD10 with CFD motor operator is a true workhorse fire door operating system that is both simple and efficient. The convenience of floor level drop testing and reset is showcased with this system that handles the largest fire doors with ease. The system may be activated for closure by an alarm signal or by power failure. Reset is accomplished by simply pressing the “open” button.

- Fail-safe design and operation
- UL and ULC Labeled
- For use with detectors as a stand-alone FACP or integrate to building FACP
- Floor level test and reset
- Preset time delay before closure
- Full-duty, gear reduced motor
- Limit switches are driven, eliminating resetting
- Optional battery backup
- Centrifugal governor
- Service door construction and durability

COLORS

Three standard paint finishes plus 188 powder coat finishes and stainless steel #4 finish



Colors shown may not reflect true steel color. Use for reference only. Due to the printing process colors may vary from printed samples.

OPTIONS

- UL “S Labels” with seals for air and smoke infiltration
- Fail-safe release devices
- Smoke detectors
- Alarm annunciators
- Voice annunciators
- Warning strobe lights



For more information on these and other Clopay products, call 1-800-526-4301 or visit clopaycommercial.com



©2016 Clopay Building Products Company, Inc., a Griffon company.

